



Presión de apertura: 1 bar Bajo pedido: 0,2 - 0,5 - 2 - 3 - 5 bar
 Temperaturas de trabajo permitidas sin reducción en presión para juntas planas y toricas en
 NBR : -35° hasta +100°C

Artículo	ØD1	Serie	R1	Presión de trabajo (bar)	L1	L2	L3	HEX 1	HEX 2
RHVL 6 R1/8	6	L	1/8" BSP	400	35	28	8	17	17
RHVL 8 R 1/4	8	L	1/4" BSP	400	37	30	12	19	19
RHVL 10 R 1/4	10	L	1/4" BSP	400	45,5	38,5	12	22	24
RHVL 12 R3/8	12	L	3/8" BSP	400	49,5	42,5	12	27	30
RHVL 15 R 1/2	15	L	1/2" BSP	315	52,5	45,5	14	27	32
RHVL 18 R1/2	18	L	1/2" BSP	250	57,5	50	14	36	36
RHVL 22 R3/4	22	L	3/4" BSP	250	62,5	55	16	41	46
RHVL 28 R1	28	L	1" BSP	160	70,5	63	18	50	55
RHVL 35 R1 1/4	35	L	1"1/4 BSP	160	79,5	69	20	60	60
RHVL 42 R1 1/2	42	L	1"1/2 BSP	160	80	69	22	65	70
RHVS 6 R1/4	6	S	1/4" BSP	420	38,5	31,5	12	19	19
RHVS 8 R1/4	8	S	1/4" BSP	420	38,5	31,5	12	19	19
RHVS 10 R3/8	10	S	3/8" BSP	420	45,5	38	12	22	24
RHVS 12 R3/8	12	S	3/8" BSP	420	48,5	41	12	24	27
RHVS 14 R 1/2	14	S	1/2" BSP	420	52,5	44,5	14	27	32
RHVS 16 R1/2	16	S	1/2" BSP	420	56,5	48	14	32	36
RHVS 20 R3/4	20	S	3/4" BSP	250	62,5	52	16	38	41
RHVS 25 R1	25	S	1" BSP	250	66,5	54,5	18	46	50
RHVS 30 R1 1/4	30	S	1"1/4 BSP	250	77,5	64	20	55	60
RHVS 38 R 1 1/2	38	S	1"1/2 BSP	250	85,5	69,5	22	65	70