



Presión de apertura: 1 bar

Bajo pedido: 0,2 - 0,5 - 2 - 3 - 5 bar
 Temperaturas de trabajo permitidas sin reducción en presión para juntas planas y toricas en
 NBR : -35° hasta +100°C

Artículo	ØD1	Serie	R1	Presión de trabajo (bar)	L1	L2	L3	HEX 1	HEX 2
RHZL 6 R 1/8	6	L	1/8" BSP	400	33,5	26,5	8	17	17
RHZL 8 R 1/4	8	L	1/4" BSP	400	35,5	28,5	12	19	19
RHZL 10 R 1/4	10	L	1/4" BSP	400	45,5	38,5	12	22	24
RHZL 12 R 3/8	12	L	3/8" BSP	400	47,5	40,5	12	27	30
RHZL 15 R 1/2	15	L	1/2" BSP	315	49,5	42,5	14	27	32
RHZL 18 R 1/2	18	L	1/2" BSP	250	55,5	48	14	36	36
RHZL 22 R 3/4	22	L	3/4" BSP	250	63,5	56	16	41	46
RHZL 28 R 1	28	L	1" BSP	160	71,5	64	18	50	55
RHZL 35 R 1 1/4	35	L	1"1/4 BSP	160	80,5	70	20	60	60
RHZL 42 R 1 1/2	42	L	1"1/2 BSP	160	81,5	70,5	22	65	70
RHZZ 6 R 1/4	6	S	1/4" BSP	420	38,5	31,5	12	17	19
RHZZ 8 R 1/4	8	S	1/4" BSP	420	38,5	31,5	12	17	19
RHZZ 10 R 3/8	10	S	3/8" BSP	420	45,5	38	12	22	24
RHZZ 12 R 3/8	12	S	3/8" BSP	420	48,5	41	12	24	27
RHZZ 14 R 1/2	14	S	1/2" BSP	420	51,5	43,5	14	27	32
RHZZ 16 R 1/2	16	S	1/2" BSP	420	54,5	46	14	32	36
RHZZ 20 R 3/4	20	S	3/4" BSP	250	60,5	50	16	38	41
RHZZ 25 R 1	25	S	1" BSP	250	66,5	54,5	18	46	50
RHZZ 30 R 1 1/4	30	S	1"1/4 BSP	250	77,5	64	20	55	60
RHZZ 38 R 1 1/2	38	S	1"1/2 BSP	250	87,5	71,5	22	65	70