



**TN 99**

- Raccordo intermedio a gomito
- Winkel-Verschraubungen
- Equal Elbows
- Coude égal

| Serie<br>Reihe<br>Series<br>Série | Ø Tubo<br>Rohr AD<br>Tube O.D.<br>Ø Tube<br>d <sub>t</sub> | PN  | L  | L1   | CH1 | CH2 | Simbolo di<br>ordinazione<br>Bestell-Nr.<br>Part. No.<br>Références | Peso<br>Gewicht<br>Weight<br>Poids<br>kg. x100 P. |
|-----------------------------------|--|-----|----|------|-----|-----|---|---|
| LL                                | 4  | 100 | 21 | 11   | 10  | 9   | TN 99 - 4 LL  | 2,0   |
|                                   | 5  |     | 21 | 9,5  | 12  | 9   | TN 99 - 5 LL  | 2,0   |
|                                   | 6  |     | 21 | 9,5  | 12  | 9   | TN 99 - 6 LL  | 2,2   |
|                                   | 8  |     | 23 | 11,5 | 14  | 12  | TN 99 - 8 LL  | 3,9   |
|                                   | 10   |     | 27 | 15   | 17  | 14  | TN 99 - 10 LL   | 5,2   |
|                                   | 12   |     | 25 | 13   | 19  | 17  | TN 99 - 12 LL   | 7,0   |
| L                                 | 6  | 315 | 27 | 12   | 14  | 12  | TN 99 - 6 L   | 4,2   |
|                                   | 8  |     | 29 | 14   | 17  | 12  | TN 99 - 8 L   | 5,8   |
|                                   | 10   |     | 30 | 15   | 19  | 14  | TN 99 - 10 L  | 7,7   |
|                                   | 12   |     | 32 | 17   | 22  | 17  | TN 99 - 12 L  | 9,8   |
|                                   | 15   |     | 36 | 21   | 27  | 19  | TN 99 - 15 L  | 16,0  |
|                                   | 18   |     | 40 | 23,5 | 32  | 24  | TN 99 - 18 L  | 24,0  |
|                                   | 22   | 160 | 44 | 27,5 | 36  | 27  | TN 99 - 22 L  | 32,0  |
|                                   | 28   |     | 47 | 30,5 | 41  | 36  | TN 99 - 28 L  | 42,4  |
|                                   | 35   |     | 56 | 34,5 | 50  | 41  | TN 99 - 35 L  | 76,5  |
|                                   | 42   |     | 63 | 40   | 60  | 50  | TN 99 - 42 L  | 109,0   |
| S                                 | 6  | 630 | 31 | 16   | 17  | 12  | TN 99 - 6 S   | 7,1   |
|                                   | 8  |     | 32 | 17   | 19  | 14  | TN 99 - 8 S   | 8,1   |
|                                   | 10   |     | 34 | 17,5 | 22  | 17  | TN 99 - 10 S  | 12,9  |
|                                   | 12   |     | 38 | 21,5 | 24  | 17  | TN 99 - 12 S  | 15,0  |
|                                   | 14   |     | 40 | 22   | 27  | 19  | TN 99 - 14 S  | 21,0  |
|                                   | 16   | 400 | 43 | 24,5 | 30  | 24  | TN 99 - 16 S  | 26,0  |
|                                   | 20   |     | 48 | 26,5 | 36  | 27  | TN 99 - 20 S  | 42,0  |
|                                   | 25   |     | 54 | 30   | 46  | 36  | TN 99 - 25 S  | 78,0  |
|                                   | 30   |     | 62 | 35,5 | 50  | 41  | TN 99 - 30 S  | 99,0  |
|                                   | 38   |     | 72 | 41   | 60  | 50  | TN 99 - 38 S  | 133,0   |

- Le dimensioni di ingombro si intendono a raccordo chiuso.  
- Baumaße sind ca.-Maße bei angezogener Überwurfmutter.

- Overall sizes are with closed fitting.  
- Les dimensions d'encombrement s'entendent raccord monté.