



Clase: 1,6%

Dimensiones: A=10
B=29
C=14
D=62
E=68
F=57

Temperatura: de -10 hasta +60

| Artículo | R1 | Escala (bar) |
|-------------|----------|--------------|
| MFI6304001V | 1/4" BSP | 0-1 |
| MFI63042.5V | 1/4" BSP | 0-2.5 |
| MFI6304004V | 1/4" BSP | 0-4 |
| MFI6304006V | 1/4" BSP | 0-6 |
| MFI6304010V | 1/4" BSP | 0-10 |
| MFI6304012V | 1/4" BSP | 0-12 |
| MFI6304016V | 1/4" BSP | 0-16 |
| MFI6304020V | 1/4" BSP | 0-20 |
| MFI6304025V | 1/4" BSP | 0-25 |
| MFI6304040V | 1/4" BSP | 0-40 |
| MFI6304060V | 1/4" BSP | 0-60 |
| MFI6304100V | 1/4" BSP | 0-100 |
| MFI6304160V | 1/4" BSP | 0-160 |
| MFI6304250V | 1/4" BSP | 0-250 |
| MFI6304315V | 1/4" BSP | 0-315 |
| MFI6304400V | 1/4" BSP | 0-400 |
| MFI6304600V | 1/4" BSP | 0-600 |

Manómetros y vacuómetros

Manómetros

Manómetro DN 63 vertical con glicerina (1/4" BSP)



Página: 2/2

| Artículo | R1 | Escala (bar) |
|----------|----|--------------|
|----------|----|--------------|

Con doble escala bar/psi